

Product Data Sheet

40 MIL – TECHNICAL SPECIFICATIONS

A heavy-weight fabric, reinforced polyethylene material with ½ the weight of standard 40 mil non-reinforced HDPE, but with double the physical strength properties.

Product Information

USES	A interim cover/liner
AREAS OF APPLICATION	Landfill covers, Containment liners
FEATURES/BENEFITS	 Weave: Woven Black HDPE Scrim Coating: LDPE, Coating on each side

Product Data

COMPOSITION	A heavy-weight fabric with polyethylene material that doubles the physical strength properties of standard 40 mil
COLOR	White, Black or other colored coatings available
SPECS	 ◆ WEIGHT: 14.8 oz/yd² (500g/m²) ±5% ◆ THICKNESS - ASTM D1777: Nominal 40 mil (1.0 mm), ±10% ◆ STRIP TENSILE - ASTM D7003: 2" MD 285 lb, CD 350 lb ◆ GRAB TENSILE - ASTM D7004: MD 460 lb, CD 350 lb ◆ TONGUE TEAR - ASTM D5884: large scale MD 90 lb, 4 CD 120 lb ◆ HYDROSTATIC RESISTANCE - ASTM D751: 612 psi ◆ PUNCTURE RESISTANCE - ASTM D4833: 210 lb ◆ MULLEN BURST - ASTM D751: 835 psi ◆ DIMENSIONAL STABILITY - ASTM D1204: MD -3.7%, CD -2.1% ◆ LOW TEMPERATURE FLEX - ASTM D2136: MD & CD :Pass @ -65° (-85° F) ◆ ACCELERATED UV WEATHERING - ASTM G 151/154: >90% Strength retention after 2000 hrs exposure @0.77 W/m²,or 1200 hrs exposure @1.35 W/m²/nm

^{*} While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty for fitness for a particular purpose. Our standard term & conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.